

Electrical Specifications

| | |
|-------------------------------|-------------------------------------------|
| Rated input voltage/frequency | 230-400 VAC / 50-60Hz |
| Rater input current * | 25 A |
| Cable section * | 3G6 mm ² 5G2,5 mm ² |
| Residual current protection | 30mA |

Kiosk

| | |
|--------------------------------|--------------------------------------------------------|
| Operating and Display elements | |
| Identification | RFID (Mifare/Calypso) |
| Display elements | Display 7 inches (800 x 480) Numeric Keyboard touch |

Communication

| | |
|---------------------------|------------|
| Ethernet | Yes |
| Integrated GSM/GPRS modem | Optional |
| RFID(13,56 MHz) | Yes |
| WLAN | On request |

Dimensions

| | |
|-----------|---------------------|
| W x H x D | 345 x 1600 x 170 mm |
| Weight | Aprox. 40 Kg |

Satellite

| | |
|----------------------------------|-----------------------------|
| Rater output voltage/frequency | 230VAC / 50-60Hz |
| Outlet type | 2 outlet Schuko |
| Charging mode | Mode 1, 2 (L1-N-PE) |
| Charging current/output capacity | 10 A/ 2,3 KW per outlet |
| Protection | 10 A per outlet, in kiosk |
| Energy metering | Calibrated (1Wh resolution) |
| External lighting | Leds status |

Dimensions

| | |
|-----------|---------------------|
| W x H x D | 200 x 1000 x 150 mm |
| Weight | Aprox. 17 Kg |

* For one satellite