

MCQC Technical Data**4 WHEELS CHAdeMO QUICK CHARGE****Electrical Specifications**

| | |
|--|---|
| Output Power | 50KW (other power configurations are available) 10 KW, 20 KW, 30 KW, 40 KW, 50 KW, 60 KW. |
| Rater output voltage/frequency | 380/400 VAC ± 10% 3 L-N-PE |
| Required/Available nominal input power | 58 KVA |
| Rater input current | 80 A @ 400 VAC |
| Max Output Current | 125 A @ 400VDC |
| Efficiency | >90% |
| Power factor | 1 |
| Power Converter Technology | Full Bridge High Frequency IGBT |
| Output Ground Fault Protection | Yes |

Charging Point

| | |
|----------------------------|----------------------|
| Charger Interface Standard | CHAdeMO (TEPCO) |
| Output voltage | 0 - 525 VDC |
| DC Output Connector | TEPCO-JARI Level III |
| Charger Mode | Mode 4 |

Comunication

| | |
|---------------------------|------------|
| Ethernet | Yes |
| Modem GSM/GPRS Integreted | Optional |
| RFID (13,56 MHz) | Yes |
| WLAN | On request |

Dimensions

| | |
|-----------|---------------------|
| W x H x D | 900 x 800 x 1400 mm |
| Weight | 450 Kg. |