

**Electrical Specifications**

Rater input voltage/frequency	230-400 VAC / 50-60Hz
Rater input current	40 A
Cable section	3G10 mm <sup>2</sup> 5G4 mm <sup>2</sup>
Residual current protection	30mA

**Charging Point 1**

Rater output voltage/frequency	230 VAC / 50-60Hz
Outlet Type	Outlet Type ICE 62196-2
Charging Mode	Modo 3 (L1-N-PE - 2 control signals)
Charging current/output capacity	3,7 KW - 22 KW
Protection	20 A
Plug locking	Electromechanical
Energy metering	Calibrated ( 1Wh resolution)

**Charging Point 2 (op. equal to point 1)**

Rater output voltage/frequency	230 VAC / 50-60Hz
Outlet Type	Industrial socket (L1-N-PE)
Charging Mode	Mode 1 and 2
Charging current/output capacity	16 A/ 3,7 KW
Protection	20 A
Plug locking	Electromechanical
Energy metering	Calibrated ( 1Wh resolution)

**Operating and display elements**

Identification	RFID (Mifare / Calypso)
External lighting	Yes (status indicator)
Display elements	Display 7 Inches (800 x 480) Numeric Keyboard touch Leds status (red, green, blue)

**Comunication**

Ethernet	Yes
Integrated GSM/GPRS modem	Optional
RFID(13,56 MHz)	Yes
WLAN	On request

**Dimensions**

W x H x D	400 x 1690 x 230 mm
Weight	Aprox. 50 Kg